



technical specification

LED strip

Only 7.7 Watts/metre power consumption delivering 47% energy saving.
High Efficacy LED 195 lm/W.
104 LEDs per metre.
ERP Class B.
24-volt input, less current less voltage drop.
6000k cool white or 3000k warm white 120° angle.
IP65 protected, 50,000 hours+ lamp life.
5-year Warranty.
Full CE certification and ROHS compliant.

Drivers

Tier 1 Meanwell drivers.
Fully serviceable quick release slide in Gear Trays.
Epoxy encapsulated fully isolated case with IP67 protection.
Constant voltage design.
Short circuit, over current, over voltage protection.
5-year Warranty.
Full CE certification and ROHS compliant.

Light Fitting

Casing sealed and certificated to IP66.
TM66 2.6 certified.
Specially designed 58mm CYCAL 80 Certified low carbon aluminium extrusion supplied up to 6000mm lengths.
Powdura ECO high performance polyester resin coating.
Concealed rear cable entry.
New 'RAPIDFIT' die cast connectors for forming longer runs.
Die cast aluminium end caps.
Standard 300mm multi brackets.
MAKROLON RE Snap-in polycarbonate 90° magnifying lens ISCC+ certified.
Full CE certificate and 5-year parts warranty.
Conforms to BS EN 60598-1:2015 and BS EN 60598-2-1:1989 'UK Deviations Only'.

(The manufacturer's reserve the right to alter specifications without prior notification).

options

Cold or Warm White LED colour.
RGB RF remote control colour change available on request.
Non-standard brackets available upon request.
Standard and non-standard colours.
Photo electrical cell switches.

Price will include: Polyester powder coated black or white and 300mm multi brackets.

Protected by UK registered design application 6021380.

Telephone: 01922 721 133

Email: Sales@portlandlighting.co.uk



Portland Lighting

Unit 2

Reedswood Park Road

Walsall

WS2 8DQ