



## options

- Cold or Warm White LED colour.
- RGB RF remote control colour change available on request.
- Non-standard brackets available upon request.
- Standard and non-standard colours.
- Photo electrical cell switches.

## technical specification

### LED strip

- Latest high lighting chip giving 1650 Lumens per metre LED output.
- Only 14.4 watts per metre power consumption 75% energy saving compared to Fluorescent.
- 24 volt input, less current less voltage drop.
- 6000k cool white or 3000k warm white 120 degree angle.
- IP65 protected, 50,000 hours+ lamp life.
- 5 year Warranty.
- Full CE certification and ROHS compliant.

### Drivers

- Epoxy encapsulated fully isolated case with IP67 protection.
- Constant voltage design.
- Short circuit, over current, over voltage protection.
- Fitted onto quick release slide in Gear Trays.
- Full CE certification and ROHS compliant.

### Light Fitting

- Specially designed 45mm aluminium extrusion supplied up to 6000mm lengths which can be joined together using cast aluminium connectors.
- Die cast aluminium end caps with rear cable entry
- Standard 300mm multi brackets.
- Snap-in polycarbonate 90 degree magnifying lens diffuser.
- Casing sealed and certificated to IP65.
- Full CE certificate and 5 year parts warranty.
- Conforms to BS EN 60598-1:2015 and BS EN 60598-2-1:1989 'UK Deviations Only'.

(The manufacturer's reserve the right to alter specifications without prior notification).

**Price will include:** Polyester powder coated black or white and 300mm multi brackets.

Protected by UK registered design application 6021380.

Telephone: **01922 721 133**  
Email: **Sales@portlandlighting.co.uk**



Portland Lighting  
**Unit 2**  
**Reedwood Park Road**  
**Walsall**  
**WS2 8DQ**